

15-213

“The course that gives CMU its Zip!”

Floating Point Sept 6, 2006

Topics

- IEEE Floating Point Standard
- Rounding
- Floating Point Operations
- Mathematical properties

Floating Point Puzzles

■ For each of the following C expressions, either:

- Argue that it is true for all argument values
- Explain why not true

```
int x = ...;
float f = ...;
double d = ...;
```

Assume neither
d nor f is NaN

- `x == (int)(float) x`
- `x == (int)(double) x`
- `f == (float)(double) f`
- `d == (float) d`
- `f == -(-f);`
- `2/3 == 2/3.0`
- `d < 0.0 ⇒ ((d*2) < 0.0)`
- `d > f ⇒ -f > -d`
- `d * d >= 0.0`
- `(d+f) - d == f`

IEEE Floating Point


IEEE Standard 754

- Established in 1985 as uniform standard for floating point arithmetic
 - Before that, many idiosyncratic formats
- Supported by all major CPUs

Driven by Numerical Concerns

- Nice standards for rounding, overflow, underflow
- Hard to make go fast
 - Numerical analysts predominated over hardware types in defining standard

Fractional Binary Numbers



Representation

- Bits to right of “binary point” represent fractional powers of 2
- Represents rational number:

$$\sum_{k=-j}^i b_k \cdot 2^k$$

Frac. Binary Number Examples

Value Representation

5-3/4	101.11_2
2-7/8	10.111_2
63/64	0.111111_2

Observations

- Divide by 2 by shifting right
- Multiply by 2 by shifting left
- Numbers of form $0.111111\dots_2$ just below 1.0
 - $1/2 + 1/4 + 1/8 + \dots + 1/2^i + \dots \rightarrow 1.0$
 - Use notation $1.0 - \varepsilon$

Representable Numbers

Limitation

- Can only exactly represent numbers of the form $x/2^k$
- Other numbers have repeating bit representations

Value

Representation

1/3

0.0101010101 [01]₂...

1/5

0.001100110011 [0011]₂...

1/10

0.0001100110011 [0011]₂...

Floating Point Representation

Numerical Form

- $-1^s M 2^E$
 - Sign bit s determines whether number is negative or positive
 - Significand M normally a fractional value in range $[1.0, 2.0)$.
 - Exponent E weights value by power of two

Encoding



- MSB is sign bit
- exp field encodes E
- frac field encodes M

Floating Point Precisions

Encoding



- MSB is sign bit
- exp field encodes E
- frac field encodes M

Sizes

- Single precision: 8 exp bits, 23 frac bits
 - 32 bits total
- Double precision: 11 exp bits, 52 frac bits
 - 64 bits total
- Extended precision: 15 exp bits, 63 frac bits
 - Only found in Intel-compatible machines
 - Stored in 80 bits
 - » 1 bit wasted

“Normalized” Numeric Values

Condition

- $\text{exp} \neq 000\dots 0$ and $\text{exp} \neq 111\dots 1$

Exponent coded as *biased* value

$$E = \text{Exp} - \text{Bias}$$

- *Exp* : unsigned value denoted by `exp`
- *Bias* : Bias value
 - » Single precision: 127 (*Exp*: 1...254, *E*: -126...127)
 - » Double precision: 1023 (*Exp*: 1...2046, *E*: -1022...1023)
 - » in general: $\text{Bias} = 2^{e-1} - 1$, where *e* is number of exponent bits

Significand coded with implied leading 1

$$M = 1.\text{xxx}\dots\text{x}_2$$

- `xxx...x`: bits of `frac`
- Minimum when `000...0` ($M = 1.0$)
- Maximum when `111...1` ($M = 2.0 - \epsilon$)
- Get extra leading bit for “free”

Normalized Encoding Example

Value

Float $F = 15213.0;$

■ $15213_{10} = 11101101101101_2 = 1.1101101101101_2 \times 2^{13}$

Significand

$M = 1.\underline{1101101101101}_2$

$\text{frac} = \underline{11011011011010000000000}_2$

Exponent

$E = 13$

$\text{Bias} = 127$

$\text{Exp} = 140 = 10001100_2$

Floating Point Representation:

Hex:	4	6	6	D	B	4	0	0
Binary:	0100	0110	0110	1101	1011	0100	0000	0000
140:	100	0110	0					
15213:				1110	1101	1011	01	

Denormalized Values

Condition

- $\text{exp} = 000\dots 0$

Value

- Exponent value $E = -\text{Bias} + 1$
- Significand value $M = 0.\text{xxx}\dots\text{x}_2$
 - $\text{xxx}\dots\text{x}$: bits of frac

Cases

- $\text{exp} = 000\dots 0, \text{frac} = 000\dots 0$
 - Represents value 0
 - Note that have distinct values $+0$ and -0
- $\text{exp} = 000\dots 0, \text{frac} \neq 000\dots 0$
 - Numbers very close to 0.0
 - Lose precision as get smaller
 - “Gradual underflow”

Special Values


Condition

- $\text{exp} = 111\dots 1$

Cases

- $\text{exp} = 111\dots 1, \text{frac} = 000\dots 0$
 - Represents value ∞ (infinity)
 - Operation that overflows
 - Both positive and negative
 - E.g., $1.0/0.0 = -1.0/-0.0 = +\infty$, $1.0/-0.0 = -\infty$
- $\text{exp} = 111\dots 1, \text{frac} \neq 000\dots 0$
 - Not-a-Number (NaN)
 - Represents case when no numeric value can be determined
 - E.g., $\text{sqrt}(-1)$, $\infty - \infty$, $\infty * 0$


Summary of Floating Point Real Number Encodings



Tiny Floating Point Example

8-bit Floating Point Representation

- the sign bit is in the most significant bit.
 - the next four bits are the exponent, with a bias of 7.
 - the last three bits are the `frac`
- **Same General Form as IEEE Format**
- normalized, denormalized
 - representation of 0, NaN, infinity



Values Related to the Exponent

Exp	exp	E	2^E	
0	0000	-6	1/64	(denorms)
1	0001	-6	1/64	
2	0010	-5	1/32	
3	0011	-4	1/16	
4	0100	-3	1/8	
5	0101	-2	1/4	
6	0110	-1	1/2	
7	0111	0	1	
8	1000	+1	2	
9	1001	+2	4	
10	1010	+3	8	
11	1011	+4	16	
12	1100	+5	32	
13	1101	+6	64	
14	1110	+7	128	
15	1111	n/a		(inf, NaN)

Dynamic Range


	s	exp	frac	E	Value		
Denormalized numbers	0	0000	000	-6	0		
	0	0000	001	-6	$1/8 * 1/64 = 1/512$	← closest to zero	
	0	0000	010	-6	$2/8 * 1/64 = 2/512$		
	...						
	0	0000	110	-6	$6/8 * 1/64 = 6/512$		
	0	0000	111	-6	$7/8 * 1/64 = 7/512$	← largest denorm	
						
	0	0001	000	-6	$8/8 * 1/64 = 8/512$	← smallest norm	
	0	0001	001	-6	$9/8 * 1/64 = 9/512$		
	...						
Normalized numbers	0	0110	110	-1	$14/8 * 1/2 = 14/16$		
	0	0110	111	-1	$15/8 * 1/2 = 15/16$	← closest to 1 below	
	0	0111	000	0	$8/8 * 1 = 1$		
	0	0111	001	0	$9/8 * 1 = 9/8$	← closest to 1 above	
	0	0111	010	0	$10/8 * 1 = 10/8$		
	...						
	0	1110	110	7	$14/8 * 128 = 224$		
	0	1110	111	7	$15/8 * 128 = 240$	← largest norm	
						
	0	1111	000	n/a	inf		

Distribution of Values

6-bit IEEE-like format

- $e = 3$ exponent bits
- $f = 2$ fraction bits
- Bias is 3


Notice how the distribution gets denser toward zero.



Distribution of Values (close-up view)

6-bit IEEE-like format

- $e = 3$ exponent bits
- $f = 2$ fraction bits
- Bias is 3



Interesting Numbers

Description	exp	frac	Numeric Value
Zero	00...00	00...00	0.0
Smallest Pos. Denorm.	00...00	00...01	$2^{-\{23,52\}} \times 2^{-\{126,1022\}}$
<ul style="list-style-type: none"> ■ Single $\approx 1.4 \times 10^{-45}$ ■ Double $\approx 4.9 \times 10^{-324}$ 			
Largest Denormalized	00...00	11...11	$(1.0 - \epsilon) \times 2^{-\{126,1022\}}$
<ul style="list-style-type: none"> ■ Single $\approx 1.18 \times 10^{-38}$ ■ Double $\approx 2.2 \times 10^{-308}$ 			
Smallest Pos. Normalized	00...01	00...00	$1.0 \times 2^{-\{126,1022\}}$
<ul style="list-style-type: none"> ■ Just larger than largest denormalized 			
One	01...11	00...00	1.0
Largest Normalized	11...10	11...11	$(2.0 - \epsilon) \times 2^{\{127,1023\}}$
<ul style="list-style-type: none"> ■ Single $\approx 3.4 \times 10^{38}$ ■ Double $\approx 1.8 \times 10^{308}$ 			

Special Properties of Encoding

FP Zero Same as Integer Zero

- All bits = 0

Can (Almost) Use Unsigned Integer Comparison

- Must first compare sign bits
- Must consider $-0 = 0$
- NaNs problematic
 - Will be greater than any other values
 - What should comparison yield?
- Otherwise OK
 - Denorm vs. normalized
 - Normalized vs. infinity

Floating Point Operations

Conceptual View

- First compute exact result
- Make it fit into desired precision
 - Possibly overflow if exponent too large
 - Possibly round to fit into `frac`

Rounding Modes (illustrate with \$ rounding)

	\$1.40	\$1.60	\$1.50	\$2.50	-\$1.50
■ Zero	\$1	\$1	\$1	\$2	-\$1
■ Round down ($-\infty$)	\$1	\$1	\$1	\$2	-\$2
■ Round up ($+\infty$)	\$2	\$2	\$2	\$3	-\$1
■ Nearest Even (default)	\$1	\$2	\$2	\$2	-\$2

Note:

1. Round down: rounded result is close to but no greater than true result.
2. Round up: rounded result is close to but no less than true result.

Closer Look at Round-To-Even

Default Rounding Mode

- Hard to get any other kind without dropping into assembly
- All others are statistically biased
 - Sum of set of positive numbers will consistently be over- or underestimated

Applying to Other Decimal Places / Bit Positions

- When exactly halfway between two possible values
 - Round so that least significant digit is even
- E.g., round to nearest hundredth

1.2349999	1.23	(Less than half way)
1.2350001	1.24	(Greater than half way)
1.2350000	1.24	(Half way—round up)
1.2450000	1.24	(Half way—round down)

Rounding Binary Numbers

Binary Fractional Numbers

- “Even” when least significant bit is 0
- Half way when bits to right of rounding position = $100\dots_2$

Examples

- Round to nearest $1/4$ (2 bits right of binary point)

Value	Binary	Rounded	Action	Rounded Value
$2 \frac{3}{32}$	10.00011_2	10.00_2	($<1/2$ —down)	2
$2 \frac{3}{16}$	10.00110_2	10.01_2	($>1/2$ —up)	$2 \frac{1}{4}$
$2 \frac{7}{8}$	10.11100_2	11.00_2	($1/2$ —up)	3
$2 \frac{5}{8}$	10.10100_2	10.10_2	($1/2$ —down)	$2 \frac{1}{2}$

FP Multiplication

Operands

$$(-1)^{s1} M1 2^{E1} \quad * \quad (-1)^{s2} M2 2^{E2}$$

Exact Result

$$(-1)^s M 2^E$$

- **Sign s :** $s1 \wedge s2$
- **Significand M :** $M1 * M2$
- **Exponent E :** $E1 + E2$

Fixing

- **If $M \geq 2$, shift M right, increment E**
- **If E out of range, overflow**
- **Round M to fit `frac` precision**

Implementation

- **Biggest chore is multiplying significands**


FP Addition

Operands

$$(-1)^{s1} M1 2^{E1}$$

$$(-1)^{s2} M2 2^{E2}$$

- Assume $E1 > E2$



Exact Result

$$(-1)^s M 2^E$$

- Sign s , significand M :
 - Result of signed align & add
- Exponent E : $E1$

Fixing

- If $M \geq 2$, shift M right, increment E
- if $M < 1$, shift M left k positions, decrement E by k
- Overflow if E out of range
- Round M to fit `frac` precision

Mathematical Properties of FP Add

Compare to those of Abelian Group

- Closed under addition? YES
 - But may generate infinity or NaN
- Commutative? YES
- Associative? NO
 - Overflow and inexactness of rounding
- 0 is additive identity? YES
- Every element has additive inverse ALMOST
 - Except for infinities & NaNs

Monotonicity

- $a \geq b \Rightarrow a+c \geq b+c$ ALMOST
 - Except for infinities & NaNs

Math. Properties of FP Mult

Compare to Commutative Ring

- Closed under multiplication? YES
 - But may generate infinity or NaN
- Multiplication Commutative? YES
- Multiplication is Associative? NO
 - Possibility of overflow, inexactness of rounding
- 1 is multiplicative identity? YES
- Multiplication distributes over addition? NO
 - Possibility of overflow, inexactness of rounding


Monotonicity

- $a \geq b \ \& \ c \geq 0 \Rightarrow a * c \geq b * c$? ALMOST
 - Except for infinities & NaNs

Creating Floating Point Number

Steps

- Normalize to have leading 1
- Round to fit within fraction
- Postnormalize to deal with effects of rounding



Case Study

- Convert 8-bit unsigned numbers to tiny floating point format

- Example Numbers

128 10000000

15 00001101


33 00010001

35 00010011

138 10001010

63 00111111

Normalize




Requirement

- Set binary point so that numbers of form 1.xxxxx
- Adjust all to have leading one
 - Decrement exponent as shift left

Value	Binary	Fraction	Exponent
128	10000000	1.00000000	7
15	00001101	1.10100000	3
17	00010001	1.00010000	5
19	00010011	1.00110000	5
138	10001010	1.00010100	7
63	00111111	1.11111000	5

Rounding



Round up conditions

- Round = 1, Sticky = 1 \rightarrow > 0.5
- Guard = 1, Round = 1, Sticky = 0 \rightarrow Round to even

Value	Fraction	GRS	Incr?	Rounded
128	1.0000000	000	N	1.000
15	1.1010000	100	N	1.101
17	1.0001000	010	N	1.000
19	1.0011000	110	Y	1.010
138	1.0001010	111	Y	1.001
63	1.1111100	111	Y	10.000

Postnormalize

Issue

- Rounding may have caused overflow
- Handle by shifting right once & incrementing exponent

Value	Rounded	Exp	Adjusted	Result
128	1.000	7		128
15	1.101	3		15
17	1.000	4		16
19	1.010	4		20
138	1.001	7		134
63	10.000	5	1.000/6	64

Floating Point in C

C Guarantees Two Levels

`float` single precision
`double` double precision

Conversions

- Casting between `int`, `float`, and `double` changes numeric values
- Double or `float` to `int`
 - Truncates fractional part
 - Like rounding toward zero
 - Not defined when out of range or NaN
 - » Generally sets to TMin
- `int` to `double`
 - Exact conversion, as long as `int` has ≤ 53 bit word size
- `int` to `float`
 - Will round according to rounding mode

Curious Excel Behavior

	Number	Subtract 16	Subtract .3	Subtract .01
Default Format	16.31	0.31	0.01	-1.2681E-15
Currency Format	\$16.31	\$0.31	\$0.01	(\$0.00)

- Spreadsheets use floating point for all computations
- Some imprecision for decimal arithmetic
- Can yield nonintuitive results to an accountant!

Summary

IEEE Floating Point Has Clear Mathematical Properties

- Represents numbers of form $M \times 2^E$
- Can reason about operations independent of implementation
 - As if computed with perfect precision and then rounded
- Not the same as real arithmetic
 - Violates associativity/distributivity
 - Makes life difficult for compilers & serious numerical applications programmers